

Leaders in Precision Measurement Antennas

Delivering advanced broadband solutions for the most demanding measurement challenges worldwide



END-TO-END PRODUCTION



OVER 20 YEARS ON THE MARKET



INNOVATIVE TECHNOLOGIES



CUSTOMIZED SOLUTIONS

Single Polarized Antennas



DHR110

14 GHz - 110 GHz

VSWR_{max} < 2.1 Gain 6.5 – 18.5 dBi Power (CW/Peak) 4 W/8 W 1.00 mm_{female}



DRH30

2.5 MHz - 30 GHz

VSWR_{max} < 1.55 Gain 6 – 20 dBi Power (CW/Peak) 25 W/50 W K_{female}



DRH370

370 MHz - 6 GHz

VSWR _{max} < 1.6 Gain 3.5 – 16 dBi Power (CW/Peak) 350 W/500 W N _{female}



DRH67

6 GHz - 67 GHz

VSWR_{max} < 1.9 Gain 7 – 21.5 dBi Power (CW/Peak) 5 W/10 W 1.85 mm_{female}



DRH20E

1.6 MHz - 20 GHz

VSWR_{max} < 1.5 Gain 5 – 17 dBi Power (CW/Peak) 50 W/100 W SMA_{female}



DRH300

300 MHz - 4.5 GHz

VSWR_{max} < 1.6 Gain 4 – 15 dBi Power (CW/Peak) 800 W/1200 W N_{female}



DRH50

4.5 GHz - 50 GHz

VSWR_{max} < 1.55 Gain 6 – 20.5 dBi Power (CW/Peak) 10 W/20 W 2.40 mm_{female}



DRH18-E

1 GHz – 18 GHz

VSWR_{max} < 2.2 Gain 6 – 15 dBi Power (CW/Peak) 100 W/170 W N or SMA_{female}



DRH203

200 MHz – 3 GHz

VSWR_{max} < 1.8 Gain 3 – 16 dBi Power (CW/Peak) 1000 W/1500 W N_{female}



DRH40

4 GHz - 40 GHz

VSWR_{max} < 1.6 Gain 7 – 20 dBi Power (CW/Peak) 15 W/30 W K_{female}



DRH18-EX

800 MHz - 18 GHz

VSWR_{max} < 2.5 Gain 2.5 – 15 dBi Power (CW/Peak) 100 W/170 W N or SMA_{female}



DRH200

180 MHz – 2.2 GHz

VSWR_{max} < 1.6 Gain 6 – 14 dBi Power (CW/Peak) 1500 W/1900 W N_{female}



DRH0532

5 GHz - 32 GHz

VSWR_{max} < 1.5 Gain 7 – 21 dBi Power (CW/Peak) 25 W/50 W K_{female}



DRH10

740 MHz - 10.5 GHz

VSWR_{max} < 1.8 Gain 4 – 17 dBi Power (CW/Peak) 150 W/250 W N_{female}



TEMH20

1 GHz – 22 GHz

VSWR_{max} < 2.6 Gain 6 – 22 dBi Power (CW/Peak) 25 W/50 W 3.5 mm_{female}

Outdoor Antennas

These antennas are housed in custom-designed protective radomes that combine superior weather resistance with exceptional durability and guaranteed low electromagnetic interference in all operating conditions.

Within these radomes, the antennas deliver precise measurements and superior signal reception across a broad range of frequency applications. We can customize and tailor the radome to cover any of our antennas according to customer requirements.



ORH18R

1 GHz - 18 GHz

VSWR_{max} < 2.5 Gain 3 – 17 dBi Power (CW/Peak) 100 W/170 W 2 × SMA_{female}

ORHIIR

730 MHz - 11 GHz

VSWR_{max} < 2.4 Gain 3 – 15 dBi Power (CW/Peak) 100 W/170 W 2 × SMA_{female}

DRH18-ER

1 GHz – 18 GHz

VSWR_{max} < 2.2 Gain 6 – 15 dBi Power (CW/Peak) 100 W/170 W SMA_{female}

DRH18-EXR

800 MHz - 18 GHz

VSWR_{max} < 2.4 Gain 2.5 – 15 dBi Power (CW/Peak) 100 W/170 W SMA_{female}

DRH10R

740 MHz - 10.5 GHz

VSWR_{max} < 2.4 Gain 3 – 16 dBi Power (CW/Peak) 150 W/250 W SMA_{female}

Dual Polarized Antennas



ORH67E

6 GHz - 67 GHz

VSWR_{max} < 2.4 Gain 3 – 14 dBi Power (CW/Peak) 5 W/10 W 2 × 1.85 mm_{female}



QRH18

1 GHz - 18 GHz

VSWR_{max} < 2.5 Gain 5 – 16 dBi Power (CW/Peak) 100 W/170 W 2 × SMA_{female}



ORH50E

5 GHz - 50 GHz

 $\begin{array}{l} {\rm VSWR_{max}} < 2.5 \\ {\rm Gain} \ 4-14 \ dBi \\ {\rm Power} \ ({\rm CW/Peak}) \\ {\rm 5 \ W/10 \ W} \\ {\rm 2 \times 2.40 \ mm_{female}} \end{array}$



ORH11

730 MHz - 11 GHz

VSWR_{max} < 2.4 Gain 3 – 15.5 dBi Power (CW/Peak) 100 W/170 W 2 × SMA_{female}



ORH40

4 GHz - 40 GHz

VSWR_{max} < 2.4 Gain 6 – 16 dBi Power (CW/Peak) 10 W/20 W 2 × K_{female}



ORH400

400 MHz - 6 GHz

VSWR_{max} < 2.3 Gain 4 – 15 dBi Power (CW/Peak) 500 W/700 W 2 × N_{female}



QRH0140

1 GHz - 40 GHz

VSWR $_{avg}$ < 2.4 Gain 5 – 15.5 dBi Power (CW/Peak) 10 W/20 W 2 × K_{female}



ORH300

300 MHz - 4.5 GHz

VSWR_{max} < 2.2 Gain 2 – 15 dBi Power (CW/Peak) 700 W/1100 W 2 × N_{female}



ORH0422

4 GHz - 22 GHz

VSWR_{max} < 2.4 Gain 8 – 16 dBi Power (CW/Peak) 20 W/40 W 2 × SMA_{female}

DLPP-6

VSWR_{max} < 2.5

Gain 3 - 8 dBi

10 W/20 W

2 × SMA_{female}

Power (CW/Peak)

500 MHz - 6 GHz





20 W/40 W


2 × SMA_{female}

OEOWG1831AA

17.8 GHz - 31 GHz

VSWR_{max} < 1.5 Gain 5.5 – 9.5 dBi Power (CW/Peak) 25 W/50 W K_{female}

Measurement Horn Antennas



DRH818

7.5 GHz - 18 GHz

VSWR_{max} < 1.18 Gain 18 – 21 dBi Power (CW/Peak) 1000 W/2500 W WRD750



DRH1840-16

18 GHz - 40 GHz

VSWR_{max} < 1.18 Gain 15 – 17 dBi Power (CW/Peak) 500 W/1250 W WRD180



DRH1840-22

18 GHz - 40 GHz

VSWR $_{max}$ < 1.18 Gain 20 – 23 dBi Power (CW/Peak) 500 W/1250 W WRD180

EMC Antennas



NEW

SLPP0230

200 MHz - 3 GHz

VSWR_{max} < 1.8 Gain 8,5 – 11,5 dBi Power (CW/Peak) 1000 W/2000 W 7/16_{female}



DRH0806

800 MHz - 6 GHz

VSWR_{max} < 1.8 Gain 10 – 24 dBi Power (CW/Peak) 1000 W/1300 W 7/16_{female}

Other suitable models for EMC include DRH18-E, DRH40 and more. For any challenging EMC setup, we can design and customize solutions according to specific needs.



Scan to explore our complete antenna portfolio and solutions.

High Gain Antennas



DRH1067

10 GHz - 67 GHz

VSWR_{max} < 1.8 Gain 15 – 24 dBi Power (CW/Peak) 5 W/10 W 1.85 mm_{female}



DRH0953

9 GHz - 53 GHz

VSWR_{max} < 2 Gain 13 – 25 dBi Power (CW/Peak) 10 W/20 W 2.40 mm_{female}



DRH0844

8 GHz – 44 GHz

VSWR_{max} < 2 Gain 15 – 24 dBi Power (CW/Peak) 15 W/30 W

Lens Antennas

NEW CATEGORY

Our lens antennas feature patented 3D printed technology. Introduced in 2024, this innovative solution delivers exceptional performance that surpasses traditional limitations.

Smart lens implementation significantly enhances antenna gain and performance while maintaining minimal weight and compact dimensions

We can customize and add lens technology also to different antennas according to specific requirements.



QRH11C

730 MHz - 11 GHz

 $\begin{array}{l} \text{VSWR}_{\text{max}} < 2.8 \\ \text{Gain 3 - 20 dBi} \\ \text{Power (CW/Peak)} \\ \text{100 W/170 W} \\ \text{SMA}_{\text{female}} \end{array}$



ORH20EC

1.7 GHz - 20 GHz

VSWR_{max} < 2.4 Gain 5 – 22 dBi Power (CW/Peak) 20 W/40 W SMA_{female}



ORH40C

4 GHz - 40 GHz

 $VSWR_{max} < 2.4$ Gain 6 – 22 dBi Power (CW/Peak) 10 W/20 W K_{female}



DRH10C

740 MHz - 10.5 GHz

VSWR_{max} < 2.2 Gain 4 – 22 dBi Power (CW/Peak) 150 W/250 W N_{female}



DRH18-EC

1 GHz - 18 GHz

VSWR _{max} 2.5 Gain 5 – 23 dBi Power (CW/Peak) 100 W/170 W N or SMA_{female}



DRH20EC

1.6 GHz - 20 GHz

VSWR_{max} < 2.2 Gain 6 – 24 dBi Power (CW/Peak) 50 W/100 W SMA_{female}



DRH30C

2.5 GHz - 30 GHz

VSWR_{max} < 1.6 Gain 5 – 22 dBi Power (CW/Peak) 25 W/50 W K_{female}



DRH0844C

8 GHz - 44 GHz

VSWR_{max} < 2.2 Gain 16 – 29 dBi Power (CW/Peak) 15 W/30 W K_{female}

Circular Polarized Antennas



CDHC1015

10 GHz - 15 GHz

VSWR_{max} < 1.6 Gain 3 – 7 dBi Power (CW/Peak) 5 W/10 W 2 × SMA_{female}



SH38-07

37.5 GHz - 39 GHz

 $\begin{array}{l} \text{VSWR}_{\text{max}} < 1.8 \\ \text{Gain 7 dBi} \\ \text{Power (CW/Peak)} \\ 15 \text{ W/30 W} \\ \text{K}_{\text{female}} \end{array}$



SH4652-07

46 GHz - 52 GHz

 $\begin{array}{l} {\rm VSWR_{max}}\!<\!1.6\\ {\rm Gain}\,7\,{\rm dBi}\\ {\rm Power}\,({\rm CW/Peak})\\ {\rm 15}\,{\rm W/30}\,{\rm W}\\ {\rm 2}\,{\rm x}\,2.40\,{\rm mm_{female}} \end{array}$

Other Products

Standard Gain Horn Antennas

High-performance measurement antennas operating with frequencies 8.2 GHz – 140 GHz, with optional surface finishes of gold plating or Bonderite 2040 coating.

Waveguide Adapters

Professional-grade RF/microwave adapters designed for precise signal transmission, covering frequency bands from 3.95 GHz – 110 GHz, with versatile connection options.

Components and Accessories

Our comprehensive range of accessories provides all essential components for your RF testing needs – from cables and stands to couplers and fixtures.









Cables Couplers

Fixtures

Advanced Antenna Measurement Chamber



Our cutting-edge antenna measurement facility features two modern anechoic chambers equipped with both far-field and near-field measurement capabilities. The system operates across an impressive frequency range of 0.7 GHz – 120 GHz (FF) and 2 GHz – 50 GHz (NF).

In the far-field configuration, we offer testing at 3m/1m distances for antenna gain, radiation patterns, and circular polarization measurements. Our near-field setup utilizes a sophisticated spherical scanning system for precise 3D radiation pattern characterization.

From mid-2025, this advanced testing facility is also available to external customers.

Custom Solutions & Designs

Beyond standard. Beyond possible. We create exceptional RF solutions that others consider impossible. Our elite R&D team excels in groundbreaking designs for advanced research, aerospace, and specialized industrial applications - wherever conventional RF technology reaches its limits. Contact us at special@rfspin.com to discuss your unique RF requirements.

CRA0507

Large-scale measuring choke ring antenna for Airbus Defence and Space



MBA007100

Biconical antenna with integrated optical system for Mercedes-Benz



NAH03012

Ultra-light antenna for energy observations by NASA



About RF SPIN

With over 20 years of industry experience, RF SPIN is a global leader in RF and microwave components. We excel in designing and producing innovative, precision broadband antennas.

Our worldwide reputation for excellence is highlighted through the selection of our products by leading companies. Renowned for deep technical expertise, RF SPIN continues at the forefront of advancing RF technology, reinforcing our status as trusted industry experts.



Preferred Partner for World-Class Clients











End-to-End Excellence in Antenna Production

Our in-house production facility brings all antenna development under one roof, ensuring complete control of every process. Each step, from design concepts to precision manufacturing and rigorous testing, reflects our dedication to excellence.



Advanced Innovation Hub

Each RF SPIN antenna begins its journey in our R&D team, where innovative ideas are transformed into cuttingedge designs. Backed by years of RF expertise and advanced industry insights, we optimize every design for superior performance and reliability.

Smart Production Powerhouse

Our state-of-the-art manufacturing facility is equipped with high-precision CNC machines and advanced metalworking equipment. Combined with digitalized processes and meticulous quality control, we ensure exceptional accuracy at every production step.

Precision Data Access

Our comprehensive measurement facilities enable detailed antenna characterization and performance validation. Each measured antenna features a unique QR code for easy access to our specialized Antenna Portal, where you'll find product specifications and technical documentation.



RF SPIN Worldwide



Portfolio Guide valid for 2025–2026

Contact

RFspin s.r.o.

Na Berance 67/2, 160 00 Prague 6 Czech Republic



+420245008847



info@rfspin.com www.rfspin.com

RF SPIN®, FiberArch® and Mopreco® are registered trademarks of RFspin s.r.o.





High-quality antennas manufactured in the Czech Republic