


**RF SPIN**

Broadband  
Antenna  
Experts

Portfolio Guide



**PRECISION ENGINEERED.**

Design · Manufacturing · Measurement

# Single Polarized Antennas



## DHR110

14 GHz – 110 GHz

VSWR<sub>max</sub> < 2.1  
Gain 6.5 – 18.5 dBi  
Power (CW/Peak)  
4 W/8 W  
1.00 mm<sub>female</sub>



## DRH67

6 GHz – 67 GHz

VSWR<sub>max</sub> < 1.9  
Gain 7 – 21.5 dBi  
Power (CW/Peak)  
5 W/10 W  
1.85 mm<sub>female</sub>



## DRH50

4.5 GHz – 50 GHz

VSWR<sub>max</sub> < 1.55  
Gain 6 – 20.5 dBi  
Power (CW/Peak)  
10 W/20 W  
2.40 mm<sub>female</sub>



## DRH40

4 GHz – 40 GHz

VSWR<sub>max</sub> < 1.6  
Gain 7 – 20 dBi  
Power (CW/Peak)  
15 W/30 W  
K<sub>female</sub>



## DRH0532

5 GHz – 32 GHz

VSWR<sub>max</sub> < 1.5  
Gain 7 – 21 dBi  
Power (CW/Peak)  
25 W/50 W  
K<sub>female</sub>



## DRH30

2.5 GHz – 30 GHz

VSWR<sub>max</sub> < 1.55  
Gain 6 – 20 dBi  
Power (CW/Peak)  
25 W/50 W  
K<sub>female</sub>



## DRH20E

1.6 GHz – 20 GHz

VSWR<sub>max</sub> < 1.5  
Gain 5 – 17 dBi  
Power (CW/Peak)  
50 W/100 W  
SMA<sub>female</sub>



## DRH18S

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.5  
Gain 6 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
N or SMA<sub>female</sub>

NEW



## DRH18-EX

800 MHz – 18 GHz

VSWR<sub>max</sub> < 2.5  
Gain 2.5 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
N or SMA<sub>female</sub>



## DRH10

740 MHz – 10.5 GHz

VSWR<sub>max</sub> < 1.8  
Gain 4 – 17 dBi  
Power (CW/Peak)  
150 W/250 W  
N<sub>female</sub>



## DRH370

370 MHz – 6 GHz

VSWR<sub>max</sub> < 1.6  
Gain 3.5 – 16 dBi  
Power (CW/Peak)  
350 W/500 W  
N<sub>female</sub>



## DRH300

300 MHz – 4.5 GHz

VSWR<sub>max</sub> < 1.6  
Gain 4 – 15 dBi  
Power (CW/Peak)  
800 W/1200 W  
N<sub>female</sub>



## DRH203

200 MHz – 3 GHz

VSWR<sub>max</sub> < 1.8  
Gain 3 – 16 dBi  
Power (CW/Peak)  
1000 W/1500 W  
N<sub>female</sub>



## DRH200

180 MHz – 2.2 GHz

VSWR<sub>max</sub> < 1.6  
Gain 6 – 14 dBi  
Power (CW/Peak)  
1000 W/1900 W  
N<sub>female</sub>



## DRH100

100 MHz – 1.4 GHz

VSWR<sub>max</sub> < 1.5  
Gain 4 – 16 dBi  
Power (CW/Peak)  
2000 W/3000 W  
7/16<sub>female</sub>

NEW

# Outdoor Antennas



## QRH18R

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.5  
Gain 3 – 17 dBi  
Power (CW/Peak)  
100 W/170 W  
2 × SMA<sub>female</sub>



## QRH11R

730 MHz – 11 GHz

VSWR<sub>max</sub> < 2.4  
Gain 3 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
2 × SMA<sub>female</sub>



## DRH18-ER

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.2  
Gain 6 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
SMA<sub>female</sub>



## DRH18-EXR

800 MHz – 18 GHz

VSWR<sub>max</sub> < 2.4  
Gain 2.5 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
SMA<sub>female</sub>



## DRH10R

740 MHz – 10.5 GHz

VSWR<sub>max</sub> < 2.4  
Gain 3 – 16 dBi  
Power (CW/Peak)  
150 W/250 W  
SMA<sub>female</sub>



Browse our entire antenna lineup  
at [www.rfspin.com/catalog](http://www.rfspin.com/catalog).

## Dual Polarized Antennas



### QRH67E

6 GHz – 67 GHz

VSWR<sub>max</sub> < 2.4  
Gain 3 – 14 dBi  
Power (CW/Peak)  
5 W/10 W  
2 × 1.85 mm<sub>female</sub>



### QRH50E

5 GHz – 50 GHz

VSWR<sub>max</sub> < 2.5  
Gain 4 – 14 dBi  
Power (CW/Peak)  
5 W/10 W  
2 × 2.40 mm<sub>female</sub>



### QRH40

4 GHz – 40 GHz

VSWR<sub>max</sub> < 2.4  
Gain 6 – 16 dBi  
Power (CW/Peak)  
10 W/20 W  
2 × K<sub>female</sub>



### QRH0140

1 GHz – 40 GHz

VSWR<sub>avg</sub> < 2.4  
Gain 5 – 15.5 dBi  
Power (CW/Peak)  
10 W/20 W  
2 × K<sub>female</sub>



### QRH0422

4 GHz – 22 GHz

VSWR<sub>max</sub> < 2.4  
Gain 8 – 16 dBi  
Power (CW/Peak)  
20 W/40 W  
2 × SMA<sub>female</sub>



### QRH20E

1.7 GHz – 20 GHz

VSWR<sub>max</sub> < 2.4  
Gain 5 – 15.5 dBi  
Power (CW/Peak)  
20 W/40 W  
2 × SMA<sub>female</sub>



### QRH18E

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.5  
Gain 5 – 16 dBi  
Power (CW/Peak)  
100 W/170 W  
2 × SMA<sub>female</sub>



### QRH11

730 MHz – 11 GHz

VSWR<sub>max</sub> < 2.4  
Gain 3 – 15.5 dBi  
Power (CW/Peak)  
100 W/170 W  
2 × SMA<sub>female</sub>



### QRH400

400 MHz – 6 GHz

VSWR<sub>max</sub> < 2.3  
Gain 4 – 15 dBi  
Power (CW/Peak)  
500 W/700 W  
2 × N<sub>female</sub>



### QRH300

300 MHz – 4.5 GHz

VSWR<sub>max</sub> < 2.2  
Gain 2 – 15 dBi  
Power (CW/Peak)  
700 W/1100 W  
2 × N<sub>female</sub>



### DLPP-6

500 MHz – 6 GHz

VSWR<sub>max</sub> < 2.5  
Gain 3 – 8 dBi  
Power (CW/Peak)  
10 W/20 W  
2 × SMA<sub>female</sub>



### OEQWG1831AA

17.8 GHz – 31 GHz

VSWR<sub>max</sub> < 1.5  
Gain 5.5 – 9.5 dBi  
Power (CW/Peak)  
25 W/50 W  
K<sub>female</sub>

## High Gain Antennas



### DRH1067

10 GHz – 67 GHz

VSWR<sub>max</sub> < 1.8  
Gain 15 – 24 dBi  
Power (CW/Peak)  
5 W/10 W  
1.85 mm<sub>female</sub>



### DRH0953

9 GHz – 53 GHz

VSWR<sub>max</sub> < 2  
Gain 13 – 25 dBi  
Power (CW/Peak)  
10 W/20 W  
2.40 mm<sub>female</sub>



### DRH0844

8 GHz – 44 GHz

VSWR<sub>max</sub> < 2  
Gain 15 – 24 dBi  
Power (CW/Peak)  
15 W/30 W  
K<sub>female</sub>



### DRH818

7.5 GHz – 18 GHz

VSWR<sub>max</sub> < 1.18  
Gain 18 – 21 dBi  
Power (CW/Peak)  
1000 W/2500 W  
WRD750



### DRH1840-16

18 GHz – 40 GHz

VSWR<sub>max</sub> < 1.18  
Gain 15 – 17 dBi  
Power (CW/Peak)  
500 W/1250 W  
WRD180



### DRH1840-22

18 GHz – 40 GHz

VSWR<sub>max</sub> < 1.18  
Gain 20 – 23 dBi  
Power (CW/Peak)  
500 W/1250 W  
WRD180

## EMC Antennas



### BIA300-10

30 MHz – 300 MHz

VSWR<sub>max</sub> < 15  
Gain -12 – 5 dBi  
Power (CW/Peak)  
10 W/20 W  
N<sub>female</sub>



### MBA007100

70 MHz – 1 GHz

VSWR<sub>max</sub> < 10  
Gain 3 – 4 dBi  
Power (CW/Peak)  
200 W/300 W  
N<sub>female</sub>



### SLPP0230

200 MHz – 3 GHz

VSWR<sub>max</sub> < 1.8  
Gain 8.5 – 11.5 dBi  
Power (CW/Peak)  
1000 W/2000 W  
7/16<sub>female</sub>



### LPP0230

200 MHz – 3 GHz

VSWR<sub>max</sub> < 2.2  
Gain 3.5 – 8.5 dBi  
Power (CW/Peak)  
100 W/200 W  
N<sub>female</sub>



### LPP0380

300 MHz – 8 GHz

VSWR<sub>max</sub> < 2.2  
Gain 2 – 7 dBi  
Power (CW/Peak)  
40 W/80 W  
N<sub>female</sub>



### DRH0806

800 MHz – 6 GHz

VSWR<sub>max</sub> < 1.8  
Gain 10 – 24 dBi  
Power (CW/Peak)  
1000 W/1300 W  
7/16<sub>female</sub>

## Other Horn Antennas

## Lens Antennas



### QRH11C

730 MHz – 11 GHz

VSWR<sub>max</sub> < 2.8  
Gain 3 – 20 dBi  
Power (CW/Peak)  
100 W/170 W  
SMA<sub>female</sub>



### QRH18EC

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.8  
Gain 5 – 23 dBi  
Power (CW/Peak)  
100 W/170 W  
SMA<sub>female</sub>



### QRH20EC

1.7 GHz – 20 GHz

VSWR<sub>max</sub> < 2.4  
Gain 5 – 22 dBi  
Power (CW/Peak)  
20 W/40 W  
SMA<sub>female</sub>



### QRH40C

4 GHz – 40 GHz

VSWR<sub>max</sub> < 2.4  
Gain 6 – 22 dBi  
Power (CW/Peak)  
10 W/20 W  
K<sub>female</sub>



### DRH10C

740 MHz – 10.5 GHz

VSWR<sub>max</sub> < 2.2  
Gain 4 – 22 dBi  
Power (CW/Peak)  
150 W/250 W  
N<sub>female</sub>



### DRH18-EC

1 GHz – 18 GHz

VSWR<sub>max</sub> < 2.5  
Gain 5 – 23 dBi  
Power (CW/Peak)  
100 W/170 W  
N or SMA<sub>female</sub>



### DRH20EC

1.6 GHz – 20 GHz

VSWR<sub>max</sub> < 2.2  
Gain 6 – 24 dBi  
Power (CW/Peak)  
50 W/100 W  
SMA<sub>female</sub>



### DRH30C

2.5 GHz – 30 GHz

VSWR<sub>max</sub> < 2.5  
Gain 5 – 22 dBi  
Power (CW/Peak)  
25 W/50 W  
K<sub>female</sub>



### DRH40C

4 GHz – 40 GHz

VSWR<sub>max</sub> < 2.5  
Gain 6 – 22 dBi  
Power (CW/Peak)  
15 W/30 W  
K<sub>female</sub>



### DRH0844C

8 GHz – 44 GHz

VSWR<sub>max</sub> < 2.2  
Gain 16 – 29 dBi  
Power (CW/Peak)  
15 W/30 W  
K<sub>female</sub>

## Circular Polarized Antennas



### CDHC1015

10 GHz – 15 GHz

VSWR<sub>max</sub> < 1.6  
Gain 3 – 7 dBi  
Power (CW/Peak)  
5 W/10 W  
2 × SMA<sub>female</sub>



### SH38-07

37.5 GHz – 39 GHz

VSWR<sub>max</sub> < 1.4  
Gain 7 dBi  
Power (CW/Peak)  
15 W/30 W  
K<sub>female</sub>



### SH4652-07

46 GHz – 52 GHz

VSWR<sub>max</sub> < 1.6  
Gain 7 dBi  
Power (CW/Peak)  
15 W/30 W  
2 × 2.40 mm<sub>female</sub>

## Lightweight Antennas



NEW

### QRH300-EX

300 MHz – 1.7 GHz

VSWR<sub>max</sub> < 2.2  
Gain 6 – 14 dBi  
Power (CW/Peak)  
700 W/1100 W  
N<sub>female</sub>



NEW

### QRH400L

400 MHz – 6 GHz

VSWR<sub>max</sub> < 2.3  
Gain 4 – 15 dBi  
Power (CW/Peak)  
500 W/700 W  
N<sub>female</sub>



NEW

### QRH0218

2 GHz – 18 GHz

VSWR<sub>max</sub> < 2.2  
Gain 6 – 15 dBi  
Power (CW/Peak)  
100 W/170 W  
SMA<sub>female</sub>

## Other Products

### Standard Gain Horn Antennas

High-performance 8.2–140 GHz measurement antennas with gold plating or Bonderite 2040 coating providing specialized surface finishes.

### Waveguide Adapters

Professional-grade adapters for precise transmission covering frequency bands from 3.95 to 110 GHz with an extensive selection of versatile connection types.

### Mounting & Positioning

Durable tripods and adjustable mounts ensuring stable and accurate antenna alignment for repeatable results and high-precision testing.

### RF Cables & Connectivity


Professional-grade, low-loss coaxial cables and assemblies designed for high-frequency applications requiring maximum signal clarity.

### Hybrid Couplers

Specialized couplers for circular polarization applications, providing high isolation and excellent phase balance for optimal performance.

# Advanced Antenna Measurements

Our in-house anechoic chamber is a high-performance facility that guarantees the precision of every antenna we manufacture. Designed for full characterization up to 120 GHz, it serves as the primary verification hub for our own production as well as external measurement projects. This ensures that every product leaving our facility meets the highest industry standards.



## Advanced Far-Field Testing

High-accuracy measurement of gain, 3D radiation patterns, and polarization at 3 m and 1 m distances.

## High-Precision Calibration

We deliver repeatable, certified results that serve as a solid foundation for your R&D and technical documentation.

## Premium Technology

Our laboratory is powered by industry-leading instrumentation from **Anritsu**, **Rohde & Schwarz**, and **Keysight** to ensure uncompromising measurement standards.


Our measurement services are also fully available to external customers, providing expert technical support for every project.

## Data & Certification

A calibration certificate is standard for every antenna. Depending on your technical or regulatory requirements, each antenna model is available in three levels of data precision.



See more at [www.rfspin.com/antenna-data-certification](http://www.rfspin.com/antenna-data-certification).



### PROFESSIONAL CHOICE

#### ESSENTIAL

##### Simulated Performance

Standard datasets (PDF) based on high-fidelity EM models and verified performance benchmarks.

#### PLUS

##### Individual Measurement

Comprehensive characterization of your specific unit in our anechoic chambers, delivered in multiple digital formats.


#### PLUS ACCREDITED

##### Accredited Certification

Full individual measurement dataset, issued with an accredited laboratory certificate for regulated and mission-critical applications.

## RF SPIN Antenna Portal

Your measurement results don't end with a printed report. The RF SPIN Antenna Portal safeguards your antenna's digital DNA in a permanent, lifetime archive – making your data as durable as your hardware.



## All-in-One Performance Data

View complete characterization results, calibration certificates, and technical reports for your antenna unit – all safely stored in one place, available anytime.

## Simple Access

Scan the unique QR code on the unit or enter its 4-character token at [www.rfspin.com/ap](http://www.rfspin.com/ap) to instantly retrieve your antenna's full performance data.

# End-to-End Production

Full control from concept to final delivery. By managing the entire development cycle in-house, we eliminate technical discrepancies and ensure that each antenna meets the highest standards of quality and performance.




R&D & Simulation



Precise Manufacturing



Quality Assurance



Antenna Measurements



## Custom RF Solutions

Standard off-the-shelf antennas often fall short. From atypical frequencies to extreme environments, we provide custom engineering for unique challenges.

We transform concepts into high-performance hardware. Contact us to discuss your project and optimize your specific RF performance.

# About RF SPIN

20+ Years of RF Excellence. RF SPIN is a global leader in innovative, precision broadband antennas, built on deep technical expertise and long-term partnerships with industry leaders worldwide.



Mercedes-Benz



## RF SPIN Worldwide



Portfolio Guide valid for 2026-2027

## Contact

**RFspin s.r.o.**

Na Berance 67/2, 160 00 Prague 6  
Czech Republic

 +420 245 008 847

 [info@rfspin.com](mailto:info@rfspin.com)  
[www.rfspin.com](http://www.rfspin.com)

RF SPIN®, FiberArch® and Mopreco® are registered trademarks of RFspin s.r.o.



Manufactured in Czechia

